Model:

Traditional Reach-In's:

S-23F

Reach-In Solid Swing Door Freezer





## S-23F

- Stainless steel interior and exterior retains attractive finish longer.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Standard door features:
   Heavy-duty pull handle
   Each door with two spring hinges, this make the door self-closing with with enduring quality
- R290 Refrigeration system holds -8°F to 0°F (-22°C to -18°C) for the best in food preservation.
- Electronic control system:
   Adjustable temperature set point and defrost frequency
   Error codes to diagnose service issues
- Shelf: Adjustable, heavy duty PVC coated shelves.
- Standard heavy-duty casters make it easy to move and clean underneath

## Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

#### Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

			Cabin	nsions						
			(inches)			CAP.				
			(mm)			CU.FT.				
Model	Doors	Shelves	L	D	Ι	LITER	HP	Voltage	Amps	NEMA Config.
S-23F	1	3	29 736	32-1/4 818	82-1/2 2095	23 650	1/2+	115/60/1	7.92	5-15P (i)

Plug type varies by country.





CONFORMS TO NSF/ANSI STD. 7

# **S**\**3**\

## S-23F Plan View





