Model:

# **Traditional Reach-In's:**

S-23R

Reach-In Solid Swing Door Refrigerator





### S-23R

- Stainless steel interior and exterior retains attractive finish longer.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Standard door features:
   Heavy-duty pull handle
   Each door with two spring hinges, this make the door self-closing with with enduring quality
- R290 Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- Electronic control system:
   Adjustable temperature set point and defrost frequency
   Error codes to diagnose service issues
- Shelf: Adjustable, heavy duty PVC coated shelves.
- Standard heavy-duty casters make it easy to move and clean underneath

# Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

#### Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

			Cabir	nsions						
			(inches)			CAP.				
			(mm)			CU.FT.				
Model	Doors	Shelves	L	D	Н	LITER	ΗP	Voltage	Amps	NEMA Config.
			29	32-1/4	82-1/2	23				
S-23R	1	3	736	818	2095	650	1/4+	115/60/1	2.76	5-15P

Plug type varies by country.





**CONFORMS TO NSF/ANSI STD. 7** 

SABA

# S-23R Plan View







