

Model:

Traditional Reach-In's:

S-47FG

Reach-In Glass Swing Door Stainless Steel Freezer



S-47FG

- **Stainless steel interior and exterior** retains attractive finish longer.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:**
Self-closing, heavy-duty pull handle
Triple pane thermal insulated glass
Aluminum frames
- **LED Lighting**
- **R290 Refrigeration system** holds -8°F to 0°F (-22°C to -18°C) for the best in food preservation.
- **Electronic control system:**
Adjustable temperature set point and defrost frequency
Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath


Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP. CU.FT. LITER	HP	Voltage	Amps	NEMA Config.
			L	D	H					
S-47FG	2	6	54 1371	32-1/4 818	82-1/2 2095	47 1321	1-1/4	115/60/1 230-240/50/1	13.44	5-20P 

Plug type varies by country.

The depth does not includes the 2-3/8" door handle



Intertek

Intertek

CONFORMS TO NSF/ANSI STD. 7

SABA

Add: 3390 Enterprise Avenue, Hayward, CA 94545-3228

Tel: (510) 293-0189 Fax: (510) 293-0199 E-mail: info@sabacorpusa.com Website: www.sabacorpusa.com

S-47FG Plan View

