



## SCB-36

- Stainless steel interior and exterior retains attractive finish longer.Matching aluminum finished back
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Cabinet top is one piece, heavy duty reinforced stainless steel. Drip resistant "V" edge protects against spills.
- R290 Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- Electronic control system:
  Adjustable temperature set point and defrost frequency
- Standard drawer features:
  Heavy-duty pull handle
  Each drawer with tracks and rollers, this make drawer easily open and close with enduring quality
- Each drawer fits one (1)12"L x 20"W x 4"D (305 mm x 508mmx 102 mm) full size and three (3) 6"L x 6"W x 4"D (153 mm x 153 mmx 102mm)1/6size food pans.
- Standard heavy-duty casters make it easy to bear the heavy cooking equipments, move and clean underneath
- Easily accessible condenser coil for cleaning, and easy service access
- Estimated Countertop weight limit: 400 KGS / 880 lbs

## Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

			Cabinet Dimensions (inches) (mm)						Cord Length (total ft.)	
Model	Drawers	<b>GN Pans</b>	L	D	Н	Amps	HP	Voltage	(total m)	NEMA Config.
SCB-36	2	2*1/1+6*1/6		32-1/8 816	25-3/8 645	3.48	1/6	115/60/1 230-240/50/1	7.4 2.25	5-15P (i)

Plug type varies by country.





Intertek CONFORMS TO NSF/ANSI STD. 7







