Model:

24" Back Bar Cooler/Direct Draw Beer Dispenser:

SDD-24-72

Solid Swing Door Direct Draw Beer Dispenser





SDD-24-72

- CABINET CONSTRUCTION
 Standard, cabinet exterior
 construction includes attractive, wear
 resistant vinyl on steel in black finish.
 Stainless exterior options available.
 Standard interior construction utilizes
 stainless steel walls, floor and ceiling.
- REFRIGERATION
 Refrigeration system uses R290 refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.
- ELECTRICAL
 Units wired at factory and ready for connection to a 115/60/1 phase,
 15 amp dedicated outlet.
- TEMPERATURE Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)

MODEL FEATURES:

- Standard LED light inside of the cabinet
- Easily accessible condenser coil for cleaning, and easy service access
- Two-faucets column is option

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

		Cabinet Dimensions (inches / mm)			Capacity				
Model	Doors	L	D	Н	1/2 Barrels	HP	Voltage	Amps	NEMA Config.
SDD-24-72	3	72 3/4 1848	24 3/8 620	35 5/8 905	3	1/3+	115V/60Hz 220V/50Hz		5-15P

- Height does not include 15 1/4" (388mm) for draft arm.
- Plug type varies by country.
- Height does not includes 3" casters.





Intertek Intertek

CONFORMS TO NSF/ANSI STD. 7

SABA

Add: 3390 Enterprise Avenue, Hayward, CA 94545-3228

Tel: (510) 293-0189 Fax: (510) 293-0199 E-mail: info@sabacorpusa.com Website: www.sabacorpusa.com

5/2/

SDD-24-72 Plan View

