Model:

Underbar Refrigeration:

SDD-27-90

27" Direct Draw Beer Dispenser





SDD-27-90

- CABINET CONSTRUCTION
 Standard, cabinet exterior
 construction includes attractive, wear
 resistant vinyl on steel in black finish.
 Stainless exterior options available.
 Standard interior construction utilizes
 stainless steel walls, floor and ceiling.
- REFRIGERATION
 Refrigeration system uses R290 refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.
- ELECTRICAL
 Units wired at factory and ready for connection to a 115/60/1 phase,
 15 amp dedicated outlet.
- TEMPERATURE
 Oversized, factory balanced,
 refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- SANITATION
 NSF-7 approved for packaged and bottled product.

MODEL FEATURES:

- Standard LED light inside of the cabinet
- Easily accessible condenser coil for cleaning, and easy service access
- Designed to accommodate a variety of beer kegs

General Specification

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

							., - (11074 1111010 1101111001/1
			Cabinet Dimensions (inches / mm)			Capacity				
Model	Doors	Shelves	L	D	Н	1/2 Barrels	HP	Voltage	Amps	NEMA Config.
SDD-27-90	3	6	90 3/8 2295	27 3/4 705	35 5/8 905	4	1/3+	115/60/1	4.68	5-15P

• Height does not include 15 1/4" (388mm) for draft arm.





- Plug type varies by country.
- Height does not includes 3" casters.
- Two-faucets column is option



