

Model:
SDD-30-23

Underbar Refrigeration: Mobility Direct Draw Beer Dispenser

SABA



SDD-30-23

- **CABINET CONSTRUCTION**
Standard, cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish. Stainless exterior options available. Standard interior construction utilizes stainless steel walls, floor and ceiling.
- **REFRIGERATION**
Refrigeration system uses R290 refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.
- **ELECTRICAL**
Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet.
- **TEMPERATURE**
Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- **SANITATION**
NSF-7 approved for packaged and bottled product.


MODEL FEATURES:

- Standard casters for mobility
- Self-closing doors with key lock
- Reinforced stainless steel interior floor
- Side knock out plugs for gas lines
- Designed to accommodate a variety of beer kegs

General Specification

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Cabinet Dimensions (inches / mm)			Capacity 1/2 Barrels	HP	Voltage	Amps	NEMA Config.
		L	D	H					
SDD-30-23	1	23 1/2 596	30 3/4" 782	38 3/4 984	1	1/6+	115/60/1	1.92	5-15P 

● Height does not include 15 1/4" (388mm) for draft arm.

● Plug type varies by country.

● Two-faucets column is option



SABA

Add: 3390 Enterprise Avenue, Hayward, CA 94545-3228

Tel: (510) 293-0189 Fax: (510) 293-0199 E-mail: info@sabacorpusa.com Website: www.sabacorpusa.com

SDD-30-23 Plan View

SABA

