Model:

Traditional Reach-In's:

S-72RG

Reach-In Swing Glass Door Refrigerator:





S-72RG

- Stainless steel exterior retains attractive finish longer.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
 - Positive seal self-closing door.
 Duralumin door frame
 Tempering glass to protect personal safety.
- R290 Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- Electronic control system:
 Adjustable temperature set point and defrost frequency
 Error codes to diagnose service issues
- Shelf: Adjustable, heavy duty PVC coated shelves.
- Standard heavy-duty casters make it easy to move and clean underneath

Bottom mounted units feature

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

-		I									
				Cabinet Dimensions (inches) (mm)			CAP.				
	Model	Doors	Shelves	L	D	Н	CU.FT.	HP	Voltage	Amps	NEMA Config.
	S-72RG	3	9	80-7/8 2054	32-1/4 818	82-1/2 2095	72 2040	3/4+	115/60/1 230-240/50/1	10.92	5-15P (i)

C USTED US Intertek



Plug type varies by country.

The deepth does not includes the 2-3/8" door handle

CONFORMS TO NSF/ANSI STD. 7

SABA

らく さん

S-72RG Plan View

